

## Chesapeake Post Light Installation Instructions

Fixture Color:







LED Color: (





## Materials Needed:

- Power Drill with 7/16" drill bit
- Phillips Head Screwdriver
- Hammer

Note: It is assumed you have installed the power supply using its provided instructions.



- Turn the system on (if you have a photo-eye system, unplug the photo eye micro-connector from the power supply so power is provided to the lights).
- Connect the power supply to the first T-cable by plugging together the black landscape connectors.
- Drill a 7/16" hole in the riser where you want the 3 light mounted. Connect the light fixture through the hole to the micro-connector on the T-Cable.

Continued on back...

- For each additional stair light, add another T-cable by attaching the landscape plugs and repeat step 3 to install the stair light.
- Verify all lights are working and fasten each one to the stair riser with the supplied screws.
- Use the wire staples to attach the wiring to the underside of the stairs.
- If you have a photo-eye system, reconnect the photo eye when installation is complete.

\*\*\*To ensure a water tight seal, push connectors firmly together.\*\*\*

For additional product or installation assistance please call 302-294-6261.

FOR USE WITH LANDSC APE LIGHTING SYSTEM ONLY. THIS DEVICE IS ACCEPTED AS A LANDSC APE LIGHTING SYSTEM WHERE THE SUITABILITY OF THE COMBINATION SHALL BE DETERMINED BY CS A OR LOCAL INSPECTION AUTHORITIES HAVING JURISDICTION. LANDSC APE LIGHTING SYSTEMS ARE FOR OUTDOOR USE ONLY. NOT FOR USE IN DWELLING UNITS. DO NOT MOUNT POWER SUPPLY OR LUMINAIRES WITHIN 3M OF A SWIMMING POOL OR SPA. NOT FOR USE WITH SUBMERSIBLE FIXTURES. USE ONLY WITH I-LIGHTING EASY PLUG CONNECTOR CABLES AND POWER SUPPLIES. FOR ADDITIONAL CABLES PLEASE CALL 888-305-4232. THE POST LIGHTS PULL 0.7 MILLI AMPS EACH. USE ONLY 90% OF THE POWER SUPPLIES WATTAGE, ALLOWING 10% FREE. LOW VOLTAGE CABLE SHALL: BE PROTECTED BY ROUTING IN CLOSE PROXIMITY TO THE LUMINAIRE OR FITTING, OR NEXT TO A BUILDING STRUCTURE SUCH AS A HOUSE OR DECK; NOT BE BURIED EXCEPT FOR A MAXIMUM 6" (15.2CM) IN ORDER TO CONNECT TO THE MAIN LOW VOLTAGE CABLE; AND HAVE THE LENGTH CUT OFF SO THAT IT IS CONNECTED TO A CONNECTOR WITH 6" (15.2CM) FROM A BUILDING STRUCTURE, A LUMINAIRE, OR FITTING.