

Iluma Under Cabinet Installation Instructions

Fixture Color:





LED Color: (





Materials When Needed:

accommodate microconnector

Power Drill with 7/16" drill bit to Note: It is assumed you have installed the power supply using its provided instructions.



- Locate where the appropriate length light strips will be mounted.
- Clean the area with the alcohol swabs provided and let dry.
- Remove the backing of the double back tape to adhere the light strip.

Continued on back...

- Plug the connector cables together to bridge gaps between the light strips.
- Fasten the connector cables to the cabinet using the self-adhesive clips.
- Continue to mount the light strips and connecting the cables.

INSTALL LIGHTS WHILE THEY ARE ON TO GET THE BEST LIGHT PLACEMENT.

For additional product or installation assistance please call 302-294-6261.

FOR USE WITH LANDSC APE LIGHTING SYSTEM ONLY. THIS DEVICE IS ACCEPTED AS A LANDSC APE LIGHTING SYSTEM WHERE THE SUITABILITY OF THE COMBINATION SHALL BE DETERMINED BY CSA OR LOCAL INSPECTION AUTHORITIES HAVING JURISDICTION. LANDSC APE LIGHTING SYSTEMS ARE FOR OUTDOOR USE ONLY. NOT FOR USE IN DWELLING UNITS. DO NOT MOUNT POWER SUPPLY OR LUMINAIRES WITHIN 3M OF A SWIMMING POOL OR SPA. NOT FOR USE WITH SUBMERSIBLE FIXTURES. USE ONLY WITH I-LIGHTING EASY PLUG CONNECTOR CABLES AND POWER SUPPLIES. FOR ADDITIONAL CABLES PLEASE CALL 888-305-4232. THE POST LIGHTS PULL 0.7 MILLI AMPS EACH. USE ONLY 90% OF THE POWER SUPPLIES WATTAGE, ALLOWING 10% FREE. LOW VOLTAGE CABLE SHALL: BE PROTECTED BY ROUTING IN CLOSE PROXIMITY TO THE LUMINAIRE OR FITTING, OR NEXT TO A BUILDING STRUCTURE SUCH AS A HOUSE OR DECK; NOT BE BURIED EXCEPT FOR A MAXIMUM 6" (15.2CM) IN ORDER TO CONNECT TO THE MAIN LOW VOLTAGE CABLE; AND HAVE THE LENGTH CUT OFF SO THAT IT IS CONNECTED TO A CONNECTOR WITH 6" (15.2CM) FROM A BUILDING STRUCTURE, A LUMINAIRE, OR FITTING.